








# Watchdog Timer

## Selector Guide

<b>Quick Selector</b>	WDT5 TYPES WDT5-A TYPES	G-SERIES TYPES G-WDT5	WDT5D TYPES <i>Digital</i>	SM-WDT5 TYPES	M-WDT5 TYPES	P8-WDT24/PLC Types	Gx2™ SERIES
CASE SIZE	H x W x D 1.25 x 1.7 x 0.6"	H x W x D 1.64x1.92x0.48"	H x W x D 1.25 x 1.7 x 0.6"	H x W x D 1.0 x 1.7 x 0.4"	H x W x D 1.0 x 1.7 x 0.4"	H x W x D 1.5 x 2.0 x 2.0"	H x W x D 1.64x1.92x0.48"
COMPATIBILITY (FOOTPRINT)	STANDARD I/O 0.6" TYPES	"G" TYPES, FITS OPTO 22 G4, GRYHL 70G, CROUZET C4	STANDARD I/O 0.6" TYPES	MINI I/O, FITS CROUZET SM	MINI I/O, FITS GRAYHILL 70M and CROUZET M	8 Pin Octal	Gx2™ TYPES, FITS HDX™ & UNI I/O RACKS
OPERATING VOLTAGES AVAILABLE	5V LOGIC	5V, 12V, 15V, 24V	5V, 12V, 15V, 24V	5V LOGIC	5V LOGIC	24V LOGIC	5V, 12V, 15V, 24V
TIME-OUTS AVAILABLE	FIXED/Adjustable WDT5/WDT5-A	FIXED 0.1 SEC to 50 SEC	FIXED 0.031 SEC to 68 MIN	FIXED 0.1 SEC to 16 SEC	FIXED 0.1 SEC to 16 SEC	FIXED OR ADJUSTABLE	FIXED 0.1 SEC to 50 SEC
TIMING ACCURACY	+/- 15%	+/- 15%	+/- 1%	+/- 15%	+/- 15%	+/- 15%	+/- 15%
EDGE-TRIGGERED RESET	NEGATIVE EDGE	NEGATIVE EDGE	NEG/POS EDGE	NEGATIVE EDGE	NEGATIVE EDGE	POSITIVE EDGE	NEGATIVE EDGE
OPERATING TEMPERATURE	-40°C to +85°C 	-40°C to +85°C 	-10°C to +60°C 	-40°C to +85°C 	-40°C to +85°C 	-40°C to +85°C 	-40°C to +85°C 
DRY OUTPUT CONFIGURATION	FAIL OPEN (STANDARD)	FAIL OPEN (STANDARD)	FAIL OPEN (STANDARD)	FAIL OPEN (STANDARD)	FAIL OPEN (STANDARD)	FORM C (STANDARD)	FAIL OPEN/N.O. (STANDARD)
SPECIAL FEATURES	CAPTIVE #4-40 SCREW	INTEGRAL LED INDICATOR	QUARTZ TIMING, CAPTIVE SCREW	MINIATURE FOOTPRINT	MINIATURE FOOTPRINT	INPUT ACCEPTS 24V SOURCING	ADDITIONAL CONTACTS
OPTIONS	-T (SECS) -C (FAIL CLOSED) -A (adjustable)	-T (SECS) -C (FAIL CLOSED) -5A (FAIL OPEN)	-T (SECS) -C (FAIL CLOSED) -R (RESET) 50% -R1 (1 SEC RESET) -5A (FAIL-OPEN)	-T (SECS) -C (FAIL CLOSED)	-T (SECS) -C (FAIL CLOSED)	-T (SECS) -A (adjustable) -ISO (Opto Isolated) -INI (INPUT INDICATOR)	-T (SECS) -2 FORM A or B -1C (FORM 1C)
PAGE	5	5	8	5	5	13	11